

6GT | All-Around Tandem Axle Utility

Shown with Optional Spare Mount, Spare & Bi-fold Ramp Gate

GVWR: 7,000 lbs
BED LENGTHS: 12'-20'
BED WIDTH: 83"



TOP RAIL CHOICES

2-3/8" PIPE with **BALLED ENDS:**
Permanently sealed and ergonomic,
2" x 2" x 3/16" ANGLE IRON,
or 2" SQ. TUBE

FLOOR

2" Treated Lumber, installed
AFTER painting to ensure no
framing is left unfinished. Floor
is secured with 5/16" screws
and a bolt-on board cap.

GATE OPTION

48" Spring Assisted Bi-fold Ramp Gate
with ergonomic lift handles.
(48" Straight Gate, Tractor Gate, Side Gates,
and Ramps also available)

RUBBER-MOUNTED ALL LED LIGHTS

SEALED WIRING HARNESS

with molded 7-way plug

JACK

2000 lb Capacity
Top-Wind Jack with
foot, Bolted-on

COUPLER

2" - 7000 lb Sleeve-Lock

FULL WRAP TONGUE: 4" Channel

The most vulnerable part of any trailer
frame is the midsection in front of the axles.
All Diamond C tandem axle trailers have a
full-wrap tongue which reinforces the frame
all the way to the front fender brace.

STAKE POCKETS

4 Stake Pockets used
as tie down points

FRAME & CROSS MEMBERS

4" channel Frame with
2" x 11 ga square tube Cross-Members



DEXTER AXLE

2 - 3500 lb E-Z Lube,
for quick and easy
lubrication, with
1 Electric Brake

TIRES

ST205/75D15
15" x 5 Hole Wheels



Diamond C uses road-tested DuPont polyurethanes that provide
the trailers with a long-lasting, rugged, and beautiful finish.

Specifications, standard features, options, components, and colors are subject to change without notice.
Some features may be subject availability, delays, or discontinuance.

Standard Premium Dupont Paint Colors
Custom colors available upon request.

